



<b>Anziehvorschrift für Zylinderkopf</b>	<b>764.133</b>	 Das Original
<b>Tightening Instructions for Cylinder Head</b>		
<b>Instructions de serrage pour culasse</b>		
<b>Prescripciones de apriete para culatas</b>		
	passend für / suitable for adaptable à / adaptable a	<b>Mitsubishi / Hyundai</b>

Schraubenkopf / Head shape      Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete  
Tête de vis / Cabeza de tornillo



709.170  
M 10 x 100



Anziehen/ \* 30 - 35 Nm  
Tightening/ 50 - 55 Nm  
Serrage/ 70 - 75 Nm  
Apriete

Zeichenerklärung / Explanations / Explication / Explicacion

*	neue Zylinderkopfschrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)
□	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera
▶	Drehwinkel	torque angle	angle de serrage	ángulo de giro

**Motortyp / Engine type / Type de moteur / Tipo de motor**

72,5 mm Ø

Colt A151, A155    Mot.4G11, 4G16 1977>9/1986  
Colt C15A            Mot.4G11, 4G16 1977>9/1986  
Lancer A171, C11A Mot.4G11, 4G16 1977>9/1986  
Mirage              Mot.4G11, 4G16 1977>9/1986  
Colt C11, C51      Mot.4G13        8/1986>11/1989

ElringKlinger AG, Max-Eyth-Str.2  
72581 Dettingen / Erms. Tel. 07123/724 601

**\*764.133\***