




<b>Anziehvorschrift für Zylinderkopf</b>	<b>863.120</b>	 Das Original		
<b>Tightening Instructions for Cylinder Head</b>	passend für / suitable for			
<b>Instructions de serrage pour culasse</b>	adaptable à / adaptable a			
<b>Prescripciones de apriete para culatas</b>	<b>Iveco</b>			
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo				
		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete		
760.300 M 12 x 120/160				
Anziehen/ <input type="checkbox"/> 30 Nm Tightening/ * 60 Nm Serrage/ <input type="checkbox"/> 60 Nm Apriete <input checked="" type="checkbox"/> 90° <input checked="" type="checkbox"/> 90°				
Zeichenerklärung / Explanations / Explication / Explicacion				
<input checked="" type="checkbox"/> *	neue Zylinderkopfschrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos
<input checked="" type="checkbox"/> ★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)
<input type="checkbox"/> □	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo
<input checked="" type="checkbox"/> ●	Setzzeit	relaxation time	durée de tassement	tiempo de espera
<input checked="" type="checkbox"/> ►	Drehwinkel	torque angle	angle de serrage	ángulo de giro
<b>Motortyp / Engine type / Type de moteur / Tipo de motor</b>				
30.10/35.10/35.12/40.10/A40.12/45.10/A45.12/ 49.10/49.12/59.12 Turbo Daily ab 05/1996>				
Master 2,8 DTI <span style="float: right;">ab 08/1998&gt;</span>				
Mot. 8140.23/43 <span style="float: right;">2798 ccm</span>				
ElingKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601			<b>*863.120*</b>	