



FLEXCORD PLUS COOLANT

PRODUCT TYPE: COOLING SYSTEMS

RECOMMENDED FOR: Light-duty automotive coolant applications. Designed to withstand severe conditions under the bonnet. This very flexible hose is also recommended for light-duty industrial applications. The hose absorbs vibrations and shocks and has a strong, supple body.

RESISTANT TO: Resistant to the harmful conditions under the bonnet; heat, ozone and coolant additives.

CONSTRUCTION:

- SHAPE:** Straight
- TUBE:** EPDM
- REINFORCEMENT:** Aramid
- WIRE:** -
- COVER:** EPDM

STANDARDS:

- SAE NORM** -
- DIN NORM** -



TEMPERATURE:

-40°

135°

-

| Gates | PN | ↔ | | ⊘ | ↔ | ↻ | ⌚ | 💥 | 🔧 |
|--------|------------|----|--------|----|---|-----|-----|-----|---|
| | | mm | " | mm | m | mm | bar | bar | # |
| CH8X1 | 4272-10080 | 8 | 5/16 | 12 | 1 | 135 | 4 | 16 | 3 |
| CH10X1 | 4272-10100 | 10 | 3/8 | 14 | 1 | 135 | 4 | 16 | 3 |
| CH12X1 | 4272-10120 | 12 | 1/2 | 16 | 1 | 135 | 4 | 16 | 3 |
| CH15X1 | 4272-10150 | 15 | 5/8 | 19 | 1 | 120 | 4 | 16 | 3 |
| CH18X1 | 4272-10180 | 18 | 11/16 | 22 | 1 | 120 | 4 | 16 | 3 |
| CH20X1 | 4272-10200 | 20 | 13/16 | 24 | 1 | 120 | 3 | 12 | 3 |
| CH22X1 | 4272-10220 | 22 | 7/8 | 26 | 1 | 90 | 3 | 12 | 3 |
| CH25X1 | 4272-10250 | 25 | 1 | 29 | 1 | 90 | 3 | 12 | 3 |
| CH28X1 | 4272-10280 | 28 | 1 1/8 | 32 | 1 | 90 | 3 | 12 | 3 |
| CH30X1 | 4272-10300 | 30 | 1 3/16 | 34 | 1 | 90 | 3 | 12 | 3 |
| CH32X1 | 4272-10320 | 32 | 1 1/4 | 36 | 1 | 90 | 3 | 12 | 3 |
| CH35X1 | 4272-10350 | 35 | 1 3/8 | 39 | 1 | 90 | 3 | 12 | 3 |
| CH38X1 | 4272-10380 | 38 | 1 1/2 | 43 | 1 | 60 | 3 | 12 | 3 |
| CH40X1 | 4272-10400 | 40 | 1 9/16 | 45 | 1 | 60 | 2 | 8.5 | 3 |
| CH42X1 | 4272-10420 | 42 | 1 5/8 | 47 | 1 | 60 | 2 | 8.5 | 3 |
| CH45X1 | 4272-10450 | 45 | 1 3/4 | 50 | 1 | 45 | 2 | 8.5 | 3 |
| CH48X1 | 4272-10480 | 48 | 1 7/8 | 53 | 1 | 45 | 2 | 8.5 | 3 |
| CH50X1 | 4272-10500 | 50 | 2 | 55 | 1 | 45 | 2 | 8.5 | 3 |