

TEXTILE COVERED FUEL LINE HOSE

PRODUCT TYPE: FUEL SYSTEMS

RECOMMENDED FOR: Clamped hose applications on fuel systems.

Specially designed for fuel circuits (leaded and unleaded petrol, diesel) in passenger cars.

RESISTANT TO: Leaded and unleaded petrol, diesel and oil.

The cover can withstand ozone and weathering. Approved for transportation of B-7, E-5, E-10,

E-15, low sulfur diesel.

CONSTRUCTION: SHAPE: Straight

TUBE: Nitrile (NBR)

REINFORCEMENT: Textile

WIRE: -

COVER: NBR/PVC

STANDARDS: SAE NORM -

DIN NORM 73379:1982

TEMPERATURE:

. C -35°







Gates).	PN	Θ		IO		(RZ)		
		mm	"	mm	m	mm	bar	bar
TFL3.2X15	4324-10050	3.2	7/64	7	15	13	6	23
TFL4X15	4324-10051	4	5/32	9	15	15	6	23
TFL5X15	4324-10055	5	3/16	10	15	18	6	23
TFL6X15	4324-10052	6	1/4	11	15	20	6	23
TFL7X15	4324-10056	7	9/32	12	15	25	6	23
TFL8X15	4324-10053	8	5/16	13	15	25	6	23
TFL10X10	4324-10054	10	3/8	15	10	30	6	23