

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

automatic transmission fluid (ATF)
Article number: 176873, 176897, 171776

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Lubricant

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG
Wilhelmstr. 47
58256 Ennepetal / GERMANY
Phone +49 2333 911-0
Fax +49 2333 911-444
Homepage www.febi.com
E-mail info@febi.com

Address enquiries to

Technical information info@febi.com

Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.
P501 Dispose of contents/container in accordance with local/national regulation.

Special labelling

Contains: 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate. EUH208 May produce an allergic reaction.

2.3 Other hazards

Physico-chemical hazards

No particular hazards known.

Human health dangers

Frequent persistent contact with the skin can cause skin irritation.

Environmental hazards

Does not contain any PBT or vPvB substances.
Contains no ingredients with endocrine-disrupting properties.

Other hazards

none

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
20 - < 50	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based CAS: 72623-87-1, EINECS/ELINCS: 276-738-4, EU-INDEX: 649-483-00-5, Reg-No.: 01-2119474889-13-XXXX GHS/CLP: Asp. Tox. 1: H304
1 - < 5	Phenol derivates GHS/CLP: Aquatic Chronic 4: H413
1 - < 5	Bis(nonylphenyl)amine CAS: 36878-20-3, EINECS/ELINCS: 253-249-4, Reg-No.: 01-2119488911-28-XXXX GHS/CLP: Aquatic Chronic 4: H413
0.1 - < 1	4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate CAS: 93882-40-7, EINECS/ELINCS: 299-434-3, Reg-No.: 01-2120735527-50 GHS/CLP: Skin Sens. 1: H317 - Eye Irrit. 2: H319 - Aquatic Chronic 2: H411
0.01 - < 0.25	Alkyl thiophosphites EINECS/ELINCS: 424-820-7, Reg-No.: 01-0000017126-75-xxxx GHS/CLP: Skin Corr. 1B: H314 - Acute Tox. 4: H312 - Aquatic Chronic 1: H410 - Aquatic Acute 1: H400, M-Factor (chronic): 10

Comment on component parts

Contains less than 3% w/w DMSO-extract (only for mineral oils)
Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements and R-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Change soaked clothing.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact

In case of contact with skin wash off immediately with soap and water.
Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion

Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in the event of vomiting, risk of product entering the lungs.
Treat symptomatically.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not be used

Full water jet

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.
Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up residues with absorbent material (e.g. sand).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures necessary if used correctly.

The product is combustible.

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with food and animal food/diet.

Keep container tightly closed.

Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2



Ferdinand Bilstein GmbH + Co. KG

Date printed 28.02.2023, Revision 28.02.2023

Version 14.0. Supersedes version: 13.0

Page 4 / 13

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

not relevant

DNEL

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
Industrial, dermal, Long-term - systemic effects, 5 mg/kg bw/day
general population, dermal, Long-term - systemic effects, 2.5 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0.25 mg/kg bw/day
Alkyl thiophosphites
Industrial, inhalative, Long-term - systemic effects, 1.76 mg/m ³
Industrial, dermal, Long-term - systemic effects, 0.5 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0.25 mg/kg bw/day
general population, inhalative, Long-term - systemic effects, 0.43 mg/m ³
general population, dermal, Long-term - systemic effects, 0.25 mg/kg bw/day
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
Industrial, inhalative, Long-term - local effects, 5.58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m ³
general population, inhalative, Long-term - local effects, 1.19 mg/m ³
general population, inhalative, Long-term - systemic effects, 740 µg/kg bw/day
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
Industrial, inhalative, Long-term - systemic effects, 3.526 mg/m ³ (AF= 75)
Industrial, dermal, Long-term - systemic effects, 2 mg/kg bw/d (AF= 300)
general population, oral, Long-term - systemic effects, 0.5 mg/kg bw/d (AF= 600)

PNEC

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
seawater, 41.2 µg/L
sediment (freshwater), 1 mg/kg sediment dw
sediment (seawater), 0.1 mg/kg sediment dw
freshwater, 412 µg/L
Alkyl thiophosphites
oral (food), 10 mg/kg
freshwater, 900 ng/l
seawater, 90 ng/l
sewage treatment plants (STP), 54 mg/l
sediment (freshwater), 0.073 mg/kg
soil, 0.015 mg/kg
sediment (seawater), 0.007 mg/kg
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
oral (food), 9.33 mg/kg food
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7



Ferdinand Bilstein GmbH + Co. KG

Date printed 28.02.2023, Revision 28.02.2023

Version 14.0. Supersedes version: 13.0

Page 5 / 13

oral (food), 20 mg/kg food (AF=300)
freshwater, 0.009 mg/L (AF= 1000)
seawater, 0.001 mg/L (AF= 10 000)
sewage treatment plants (STP), 100 mg/L (AF= 10)
sediment (freshwater), 542 229.75 mg/kg dw
sediment (seawater), 54 222.98 mg/kg dw
soil, 259 870.48 mg/kg dw

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances. General exposure limit for oil mist should be noted.
Eye protection	If there is a risk of splashing: safety glasses (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0.4 mm; Nitrile rubber, >480 min (EN 374-1/-2/-3). > 0.4 mm; Neoprene, >480 min (EN 374-1/-2/-3).
Skin protection	light protective clothing
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin.
Respiratory protection	not applicable
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	red
Odor	characteristic
Odour threshold	not relevant
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	No information available.
Flash point [°C]	212
Flammability (solid, gas) [°C]	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/cm ³]	0.84 (15 °C / 59,0 °F)
Relative density	not determined
Bulk density [kg/m ³]	not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient [n-octanol/water]	No information available.
Kinematic viscosity	34 mm ² /s (40° C)
Relative vapour density	No information available.
Evaporation speed	No information available.
Melting point [°C]	No information available.
Auto-ignition temperature [°C]	No information available.
Decomposition temperature [°C]	No information available.
Particle characteristics	No information available.

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

No dangerous reactions known if used as directed.

10.4 Conditions to avoid

Strong heating.



Ferdinand Bilstein GmbH + Co. KG

Date printed 28.02.2023, Revision 28.02.2023

Version 14.0. Supersedes version: 13.0

Page 7 / 13

10.5 Incompatible materials

Oxidizing agent
Strong basic compounds
Strong acids.

10.6 Hazardous decomposition products

No hazardous decomposition products known.



Ferdinand Bilstein GmbH + Co. KG

Date printed 28.02.2023, Revision 28.02.2023

Version 14.0. Supersedes version: 13.0

Page 8 / 13

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Product
Based on the available information, the classification criteria are not fulfilled.
Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
LD50, oral, Rat, 5000 mg/kg bw
Alkyl thiophosphites
LD50, oral, Rat, > 2000 mg/kg
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, oral, Rat, 5000 mg/kg bw
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
LD50, oral, Rat, > 10 000 mg/kg bw

Acute dermal toxicity

Product
ATE-mix, dermal, 202.669 mg/kg bw
Substance
Alkyl thiophosphites
LD50, dermal, Rabbit, > 500 mg/kg
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw

Acute inhalational toxicity

Substance
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

Skin corrosion/irritation Based on the available information, the classification criteria are not fulfilled.

Respiratory or skin sensitisation Toxicological data of complete product are not available.
 May produce an allergic reaction.
 Calculation method

Specific target organ toxicity — single exposure Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure Based on the available information, the classification criteria are not fulfilled.

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
NOEL, oral, Rat, 100 mg/kg bw/day
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOAEC, inhalative, Rat, 980 mg/m ³ air
LOAEL, oral, Rat, 125 mg/kg bw/day

Ferdinand Bilstein GmbH + Co. KG

Date printed 28.02.2023, Revision 28.02.2023

Version 14.0. Supersedes version: 13.0

Page 9 / 13

Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	

Toxicological data of complete product are not available.
The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

11.2 Information on other hazards

Endocrine disrupting properties	Contains no ingredients with endocrine-disrupting properties.
Other information	No information available.

SECTION 12: Ecological information

12.1 Toxicity

Substance
Bis(nonylphenyl)amine, CAS: 36878-20-3
EC50, (48h), Invertebrates, 100 mg/L
EL50, (72h), Algae, 100 mg/L
NOELR, (21d), Invertebrates, 4.45 mg/L
NOELR, (33d), fish, 10 mg/L
Alkyl thiophosphites
EL50, (72h), Selenastrum capricornutum, 0.31 mg/l
EL50, (48h), Daphnia magna, 0.09 mg/l
LL50, (21d), Daphnia magna, 0.22 mg/l
LL50, (24h), Oncorhynchus mykiss, 2 mg/l
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
NOELR, (14d), fish, 1 g/L
LL50, (4d), Invertebrates, 10 g/L
LL50, (4d), fish, 100 mg/L
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate, CAS: 93882-40-7
LC50, (96h), fish, > 100 mg/l (OECD 203)
EL50, (72h), Algae, > 100 mg/l (OECD 201)
EL50, (48h), Daphnia magna, 9.5 mg/l (OECD 202)

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.



Ferdinand Bilstein GmbH + Co. KG

Date printed 28.02.2023, Revision 28.02.2023

Version 14.0. Supersedes version: 13.0

Page 10 / 13

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!
Disposal in an incineration plant in accordance with the regulations of the local authorities.
For recycling, consult manufacturer.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150102
150104
150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

Ferdinand Bilstein GmbH + Co. KG

Date printed 28.02.2023, Revision 28.02.2023

Version 14.0. Supersedes version: 13.0

Page 11 / 13

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EC 2000/532/EC; 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2023)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.

- Observe employment restrictions for people no

- VOC (2010/75/CE) 0%

15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H413 May cause long lasting harmful effects to aquatic life.
H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV®/TWA = Threshold limit value – time-weighted average
TLV®/STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position

SECTION 11 been added: Contains no ingredients with endocrine-disrupting properties.

SECTION 12 been added: Contains no ingredients with endocrine-disrupting properties.



Ferdinand Bilstein GmbH + Co. KG

Date printed 28.02.2023, Revision 28.02.2023

Version 14.0. Supersedes version: 13.0

Page 13 / 13