# Ferdinand Bilstein GmbH + Co. KG

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0 Page 1 / 12

SEC	SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1	1 Product identifier		
		Gear oil 75W - 80 Article number: 180073	
1.2	Relevant identified uses of the s	ubstance or mixture and uses advised against	
1.2.1	1 Relevant uses		
		Gearbox oil	
1.2.2	2 Uses advised against		
		None known.	
1.3	Details of the supplier of the safe	ety data sheet	
	Company	Ferdinand Bilstein GmbH + Co. KG Wilhelmstr. 47 58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-44 Homepage www.febi.com E-mail info@febi.com	
	Address enquiries to		
	Technical information	info@febi.com	
	Safety Data Sheet	info@febi.com	
1.4	Emergency telephone number		
	Advisory body	+49 (0)89-19240 (24h) (English)	
SEC	CTION 2: Hazards identification		
2.1	2.1 Classification of the substance or mixture [REGULATION (GB) CLP]		
		No classification.	
2.2	Label elements		
		The product is required to be labelled in accordance with regulation CLP.	
	Hazard pictograms	none	
	Signal word	none	
	Hazard statements	none	
	Special labelling	EUH210 Safety data sheet available on request.	
		Contains: 3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid. EUH208 May produce an allergic reaction.	
2.3	Other hazards		
	Environmental hazards	Does not contain any PBT or vPvB substances. Contains no ingredients with endocrine-disrupting properties.	
	Other hazards	No particular hazards known.	
SEC	CTION 3: Composition / Informatio	n on ingredients	
3.1	Substances		

not applicable

# Ferdinand Bilstein GmbH + Co. KG

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0 Pa

Page 2 / 12

# 3.2 Mixtures

The pro	The product is a mixture.		
Range [	%] Substance		
1 - < 10	Distillates (petrole	um), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt)	
		EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX	
_	GHS/CLP: Asp. To	ox. 1: H304	
0.1 - < 0	amines, C12-14-a		
		931-384-6, Reg-No.: 01-2119493620-38	
		Tox. 4: H302 - Eye Dam. 1: H318 - Skin Sens. 1: H317 - Aquatic Chronic 2: H411 e Dam. 1: H318, >= 9.39: Skin Sens. 1B: H317, > 50: Eye Irrit. 2: H319	
0.1 - 1		pphosphorylsulfanyl)-2-methyl-propionic acid	
0.1 - 1	· · ·	4, EINECS/ELINCS: 434-070-2, Reg-No.: 01-2119658068-31	
		am. 1: H318 - Skin Sens. 1B: H317 - Aquatic Chronic 3: H412	
Comme	nt on component parts	Contains less than 3% w/w DMSO-extract (only for mineral oils) Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%. For full text of H-statements: see SECTION 16.	
ECTION 4:	First aid measures		
1 Descri	otion of first aid measure	S	
Genera	information	Change soaked clothing.	
Inhalati	on	Ensure supply of fresh air. In the event of symptoms seek medical treatment.	
Skin co	ntact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.	
Eye cor	tact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	
Ingestic	n	Do not induce vomiting. Consult a doctor immediately. Rinse out mouth and give plenty of water to drink.	
2 Mostir	nportant symptoms and e	effects, both acute and delayed	
		Headache	
3 Indicat	ion of any immediate med	dical attention and special treatment needed	
		Treat symptomatically. Forward this sheet to your doctor.	
ECTION 5:	Fire-fighting measures		
1 Exting	uishing media		
Suitable	extinguishing media	Foam, dry powder, water spray jet, carbon dioxide.	
Extingu be used	ishing media that must not	Full water jet.	
2 Specia	I hazards arising from the	e substance or mixture	
-		Risk of formation of toxic pyrolysis products. Carbon monoxide (CO) Sulphur oxides (SOx). Nitrogen oxides (NOx).	

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0 Page 3 / 12

5.3	Advice for firefighters	
		Do not inhale explosion and/or combustion gases. Use self-contained breathing apparatus.
		Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.
SEC	TION 6: Accidental release measu	res
6.1	Personal precautions, protective	equipment and emergency procedures
		Some risk of slipping due to spillage of product. Forms slippery surfaces with water.
6.2	Environmental precautions	
		Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater.
6.3	Methods and material for contain	ment and cleaning up
		Take up with absorbent material (e.g. oil binder). Dispose of absorbed material in accordance within the regulations.
6.4	Reference to other sections	
		See SECTION 8+13
SEC	TION 7: Handling and storage	
7.1	Precautions for safe handling	
		No special measures necessary if used correctly. Use only in well-ventilated areas. Use solvent-resistant equipment.
		The product is combustible.
		Do not eat, drink or smoke when using this product. After worktime and before work breaks the affected skin areas must be thoroughly cleaned. Use barrier skin cream. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash before reuse.
7.2	Conditions for safe storage, inclu	iding any incompatibilities
		Keep only in original container. Prevent penetration into the ground.
		Do not store together with oxidizing agents.
		Keep container in a well-ventilated place. Keep container tightly closed.
7.3	Specific end use(s)	See product use, SECTION 1.2

# Ferdinand Bilstein GmbH + Co. KG

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0

Page 4 / 12

# **SECTION 8: Exposure controls / personal protection**

# 8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

not relevant

DNEL

Substance	
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4	
Industrial, dermal, Long-term - systemic effects, 1.25 mg/kg bw/d (AF=100)	
Industrial, inhalative, Long-term - systemic effects, 4.4 mg/m <sup>3</sup> (AF=25)	
general population, oral, Long-term - systemic effects, 0.6 mg/kg bw/d (AF=200)	
general population, dermal, Long-term - systemic effects, 0.6 mg/kg bw/d (AF=200)	
general population, inhalative, Long-term - systemic effects, 1.1 mg/m³ (AF=50)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CA	S: 64742-65-0
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day	
Industrial, inhalative, Long-term - local effects, 5.58 mg/m <sup>3</sup>	
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m <sup>3</sup>	
general population, oral, Long-term - local effects, 740 μg/kg bw/day	
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus amines, C12-14-alkyl (branched)	oxide, propylene oxide and
Industrial, dermal, Long-term - systemic effects, 12.5 mg/kg bw/d (AF=120)	
Industrial, inhalative, Long-term - systemic effects, 4.28 mg/m <sup>3</sup> (AF=30)	
general population, oral, Long-term - systemic effects, 0.25 mg/kg bw/d (AF=600)	
general population, dermal, Long-term - systemic effects, 6.25 mg/kg bw/d (AF=240	)
general population, inhalative, Long-term - systemic effects, 1.09 mg/m <sup>3</sup> (AF=60)	

#### PNEC

Substance
3-(Diisobutoxy-thiophosphoryIsulfanyI)-2-methyl-propionic acid, CAS: 268567-32-4
soil, 4.54 mg/kg dw
sediment (seawater), 2.3 mg/kg dw
sediment (freshwater), 23 mg/kg dw
sewage treatment plants (STP), 10 mg/l (AF=10)
seawater, 0.007 mg/L (AF=500)
freshwater, 0.072 mg/L (AF=50)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
oral (food), 9.33 mg/kg food
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
oral (food), 10 mg/kg dw (AF=300)
soil, 1.17 µg/kg dw
sediment (seawater), 1.29 µg/kg dw
sediment (freshwater), 12.9 µg/kg dw
sewage treatment plants (STP), 24.33 mg/L (AF=100)
seawater, 0.24 µg/L (AF=500)
freshwater, 2.4 µg/L (AF=50)

# Ferdinand Bilstein GmbH + Co. KG

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0 Page 5 / 12

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0.4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.
Respiratory protection	not applicable
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

	<u>.</u> <u>.</u>
Physical state	liquid
Form	liquid
Color	yellowish
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	not applicable
Flash point [°C]	241
Flammability (solid, gas) [°C]	Not explosive.
Lower explosion limit	not self-igniting
Upper explosion limit	not applicable
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/cm³]	0.85 (20 °C / 68,0 °F)
Relative density	not determined
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient [n-octanol/water]	No information available.
Kinematic viscosity	56 mm²/s 40°C (DIN 51562)
Relative vapour density	No information available.
Evaporation speed	No information available.
Melting point [°C]	No information available.
Auto-ignition temperature [°C]	not applicable
Decomposition temperature [°C]	No information available.
Particle characteristics	No information available.

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0 Page 6 / 12

#### 9.2 Other information

No information available.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

See SECTION 10.3.

### 10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

#### 10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents. Reactions with strong alkalies. Reactions with strong acids.

#### 10.4 Conditions to avoid

Strong heating.

#### 10.5 Incompatible materials

Strong oxidizing agent. See SECTION 10.3.

#### **10.6 Hazardous decomposition products**

No hazardous decomposition products known.

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0

Page 7 / 12

### **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity

Substance
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LD50, oral, Rat, > 2000 mg/kg bw
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, oral, Rat, 5000 mg/kg bw
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
LD50, oral, Rat, 2000 mg/kg

#### Acute dermal toxicity

Substance	
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4	
LD50, dermal, Rat, > 2000 mg/kg bw	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0	
LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw	

#### Acute inhalational toxicity

Substance	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0	
LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h	

#### Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Eye, non-irritating

### Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.

#### Substance

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-irritating

### Respiratory or skin sensitisation

Based on the available information, the classification criteria are not fulfilled. May produce an allergic reaction. Calculation method

Substance
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-sensitizing

Specific target organ toxicity — single exposure Specific target organ toxicity — repeated exposure		Based on the available information, the classification criteria are not fulfilled.	
		Based on the available information, the classification criteria are not fulfilled.	
	Substance		

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0 NOAEL, dermal, Rabbit, 1000 mg/kg bw/day NOAEL, inhalative, Rat, 980 mg/m<sup>3</sup> air

# Ferdinand Bilstein GmbH + Co. KG

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0 Page 8 / 12

		LOAEL, oral, Rat, 125 mg/kg bw/day	
	Mutagenicity		Based on the available information, the classification criteria are not fulfilled.
		Substance	
		Distillates (petroleu	m), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
		in vitro, negativ	
<b>Reproduction toxicity</b> Based on the available information, the classification criteria are not fulfilled.		Based on the available information, the classification criteria are not fulfilled.	
	- Fertility		
			m), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
			000 mg/kg bw/d, no adverse effect observed
	- Development		No information available.
	Carcinogenicity		Based on the available information, the classification criteria are not fulfilled.
	Aspiration hazard		Based on the available information, the classification criteria are not fulfilled.
	General remarks		
			The toxiclogical data are those of the pure product.
1.2	Information on o	other hazards	
	Endocrine disrupt	ing properties	Contains no ingredients with endocrine-disrupting properties.
	Other information		none
	TION 12. Ecologi	and information	

# **SECTION 12: Ecological information**

# 12.1 Toxicity

11

Substance
3-(Diisobutoxy-thiophosphorylsulfanyl)-2-methyl-propionic acid, CAS: 268567-32-4
LC50, (96h), fish, 54 mg/l
EC50, (48h), Daphnia magna, 53 mg/l
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOELR, (14d), fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), fish, 100 mg/L
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
LC50, (96h), fish, 24 mg/l
EC50, (48h), Daphnia magna, 91.4 mg/l

# 12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

### 12.3 Bioaccumulative potential

No information available.

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0 Page 9 / 12

#### 12.4 Mobility in soil

No information available.

# 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

### 12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

# 12.7 Other adverse effects

Ecological data of complete product are not available. Do not discharge product unmonitored into the environment or into the drainage.

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

	In according to RoHS! Disposal in an incineration plant in accordance with the regulations of the local authorities.
Waste no. (recommended)	130205* mineral-based non-chlorinated engine, gear and lubricating oils
Contaminated packaging	
	Uncontaminated packaging may be taken for recycling.
	Packaging that cannot be cleaned should be disposed of as for product.
Waste no. (recommended)	150110* packaging containing residues of or contaminated by hazardous substances

### **SECTION 14: Transport information**

.1 UN number or ID number	
Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0 Page 10 / 12

14.2	UN proper shipping name Transport by land according to	NO DANGEROUS GOODS
	ADR/RID	
	Inland navigation (ADN)	NO DANGEROUS GOODS
	Marine transport in accordance with IMDG	NOT CLASSIFIED AS "DANGEROUS GOODS"
	Air transport in accordance with IATA	NOT CLASSIFIED AS "DANGEROUS GOODS"
14.3	Transport hazard class(es)	
	Transport by land according to ADR/RID	not applicable
	Inland navigation (ADN)	not applicable
	Marine transport in accordance with IMDG	not applicable
	Air transport in accordance with IATA	not applicable
14.4	Packing group	
	Transport by land according to ADR/RID	not applicable
	Inland navigation (ADN)	not applicable
	Marine transport in accordance with IMDG	not applicable
	Air transport in accordance with IATA	not applicable
14.5	Environmental hazards	
	Transport by land according to ADR/RID	no
	Inland navigation (ADN)	no
	Marine transport in accordance with IMDG	no
	Air transport in accordance with IATA	no
14.6	Special precautions for user	

Relevant information under SECTION 6 to 8.

# 14.7 Maritime transport in bulk according to IMO instruments

not applicable

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0 Page 11 / 12

**SECTION 15: Regulatory information** 

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture		
EEC-REGULATIONS	2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014	
TRANSPORT-REGULATIONS	ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2023)	
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.	
- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.	
- VOC (2010/75/CE)	not relevant	
15.2 Chemical safety assessment		
	For this product a chemical safety assessment has not been carried out.	
SECTION 16: Other information		

# 16.1 Hazard statements (SECTION 3)

H411 Toxic to aquatic life with long lasting effects. H302 Harmful if swallowed.

- H412 Harmful to aquatic life with long lasting effects.
- H317 May cause an allergic skin reaction. H318 Causes serious eye damage.
- H304 May be fatal if swallowed and enters airways.

# Ferdinand Bilstein GmbH + Co. KG

Date printed 01.03.2023, Revision 01.03.2023



Version 2.0. Supersedes version: 1.0 Page 12 / 12

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

- IUCLID = International Uniform ChemicaL Information Database
- IVIS = In vitro irritation score

LC50 = Lethal concentration, 50% LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value - time-weighted average

TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

#### 16.3 Other information

**Classification procedure** 

Modified position

SECTION 11 been added: Contains no ingredients with endocrine-disrupting properties. SECTION 12 been added: Contains no ingredients with endocrine-disrupting properties.