

Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 1 / 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

automatic transmission fluid (ATF)

Article number: 10 92 2806, 10 93 0018, 10 92 6680, 10 92 6681

UFI: 4051-421H-000D-R1X6

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Gearbox oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company SWAG Autoteile GmbH

Am Kiesberg 4-6

42117 Wuppertal / GERMANY Phone +49 (0)202 26454-0 Fax +49 (0)202 26454-5000 Homepage www.swag.de E-mail info@swag.de

Address enquiries to

Technical information info@swag.de Safety Data Sheet info@swag.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Skin Sens. 1: H317 May cause an allergic skin reaction.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms

<u>(!</u>)

Signal word WARNING

Contains: reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl

phosphonates

1,1'-[iminobis(ethyleneiminoethylene)] bis [3-(octade cenyl) pyrrolidine-2,5-dione]

Hazard statements H317 May cause an allergic skin reaction.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P280 Wear protective gloves.

P332+P313 If skin irritation occurs: Get medical advice / attention.

P501 Dispose of contents/container to approved disposal company or municipal collection

point.

2.3 Other hazards

Human health dangers Frequent persistent contact with the skin can cause skin irritation.

Environmental hazardsDoes not contain any PBT or vPvB substances.

Contains no ingredients with endocrine-disrupting properties.

Other hazards none



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 2 / 15

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance				
30 - 60	Distillates (petroleum), hydrotreated light paraffinic				
	CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX				
	GHS/CLP: Asp. Tox. 1: H304				
5 - < 15	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract)				
	CAS: 72623-86-0, EINECS/ELINCS: 276-737-9, EU-INDEX: 649-221-00-X				
	GHS/CLP: Asp. Tox. 1: H304				
1 - < 2.5	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt)				
	CAS: 64742-65-0, EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX				
	GHS/CLP: Asp. Tox. 1: H304				
1 - < 2.5	Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract)				
	CAS: 64742-56-9, EINECS/ELINCS: 265-159-2, EU-INDEX: 649-469-00-9, Reg-No.: 01-2119480132-48-XXXX				
	GHS/CLP: Asp. Tox. 1: H304				
1 - < 2.5	Distillates (petroleum), hydrotreated light naphthenic				
	CAS: 64742-53-6, EINECS/ELINCS: 265-156-6, EU-INDEX: 649-466-00-2, Reg-No.: 01-2119480375-34-XXXX				
	GHS/CLP: Asp. Tox. 1: H304				
1 - < 2.5	reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates				
	EINECS/ELINCS: 417-450-2, EU-INDEX: 650-042-00-4, Reg-No.: 01-0000016426-70-XXXX				
	GHS/CLP: Skin Sens. 1: H317 - Aquatic Chronic 3: H412 - Eye Irrit. 2: H319 - Skin Irrit. 2: H315				
0.1 - < 1	1,1'-[iminobis(ethyleneiminoethylene)]bis[3-(octadecenyl)pyrrolidine-2,5-dione]				
	CAS: 64051-50-9, EINECS/ELINCS: 264-637-8				
	GHS/CLP: Skin Sens. 1B: H317 - Aquatic Chronic 3: H412				

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Take off contaminated clothing and wash before reuse.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact When in contact with the skin, clean with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Ingestion Seek medical advice immediately.

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in the event of vomiting, risk of product entering the lungs.

Forward this sheet to your doctor.



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 3 / 15

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.

Risk of formation of toxic pyrolysis products.

Carbon monoxide (CO) Sulphur oxides (SOx). Nitrogen oxides (NOx).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures necessary if used correctly.

The product is combustible. Fire class (DIN EN 2): B

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Cloths contaminated with product should not be kept in trouser pockets. Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 4 / 15

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container. Prevent penetration into the ground.

Do not store together with food and animal food/diet.

Do not store together with oxidizing agents.

Keep container tightly closed.

Keep container in a well-ventilated place.

Protect from heat/overheating.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

not relevant

DNEL

Substance					
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9					
Industrial, dermal, Long-term - systemic effects, 0.97 mg/kg bw/day					
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³					
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³					
general population, oral, Long-term - systemic effects, 0.74 mg/kg bw/day					
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8					
Industrial, inhalative, Long-term - local effects, 5.4 mg/m³/8h (Aerosol)					
general population, inhalative, Long-term - local effects, 1.2 mg/m³/24h (Aerosol)					
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0					
Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day					
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³					
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³					
general population, oral, Long-term - local effects, 740 μg/kg bw/day					
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6					
Industrial, dermal, Long-term - systemic effects, 0.97 mg/kg bw/day					
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³					
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³					
general population, oral, Long-term - systemic effects, 0.74 mg/kg bw/day 2.7 mg/m³					

PNEC

Substance				
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9				
oral (food), 9.33 mg/kg food				
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0				
oral (food), 9.33 mg/kg food				
Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6				
oral (food), 9.33 mg/kg food				



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 5 / 15

8.2 Exposure controls

Additional advice on system design
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

General exposure limit for oil mist should be noted.

Eye protection If there is a risk of splashing:

Safety glasses. (EN 166:2001)

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0.4 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3). > 0.4 mm: Neoprene, >480 min (EN 374-1/-2/-3).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

Respiratory protection Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards No information available.

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 6 / 15

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical stateliquidFormliquidColorred

Odor characteristic

Odour threshold No information available.

Boiling point [°C]

Flash point [°C]

Flammability (solid, gas) [°C]

Lower explosion limit

Upper explosion limit

No information available.

No information available.

No information available.

Oxidising properties no

Vapour pressure/gas pressure [kPa] < 0.01 (20°C)

Density [g/cm³] ca. 0.85 (DIN 51757) (15 °C / 59,0 °F)

Relative density not determined

Bulk density [kg/m³] not applicable

Solubility in water immiscible

Solubility other solvents No information available.

Partition coefficient [n-octanol/water] No information available.

Kinematic viscosity ca. 33 mm²/s (40°C) (DIN 51562/T1)

ca. 7.4 mm²/s (100°C)

Relative vapour density

Evaporation speed

Melting point [°C]

Auto-ignition temperature [°C]

Decomposition temperature [°C]

Particle characteristics

No information available.

No information available.

No information available.

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong acids.

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

Strong heating, because the thermal decomposition starts from > 100°C.



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 7 / 15

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

No hazardous decomposition products known.



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 8 / 15

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Product

oral, Based on the available information, the classification criteria are not fulfilled.

Substance

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0

LD50, oral, Rat, > 5000 mg/kg

reaction product of: polyethylene-polyamine-(C16-C18)-alkylamides with monothio-(C2)-alkyl phosphonates

LD50, oral, Rat, > 2000 mg/kg bw

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

LD50, oral, Rat, >5000 mg/kg bw (OECD 401)

NOAEL, oral, Rat, >1000 mg/kg bw (OECD 421)

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

LD50, oral, Rat, > 5000 mg/kg (OECD 420)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LD50, oral, Rat, 5000 mg/kg bw

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

LD50, oral, Rat, > 5000 mg/kg

Acute dermal toxicity

Product

dermal, Based on the available information, the classification criteria are not fulfilled.

Substance

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0

LD50, dermal, Rabbit, > 5000 mg/kg

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

LD50, dermal, Rabbit, >5000 mg/kg bw (OECD 403)

NOAEL, dermal, Rat, >2000 mg/kg bw (OECD 414)

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

LD50, dermal, Rabbit, > 5000 mg/kg (OECD 402)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

LD50, dermal, Rabbit, > 2000 mg/kg

Acute inhalational toxicity

Product

inhalative, Based on the available information, the classification criteria are not fulfilled.

Substance

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0

LC50, inhalative, Rat, > 5000 mg/m³ (4h)



Page 9 / 15

Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

LC50, inhalative, Rat, >5.53 mg/l air (OECD 403)

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

LC50, inhalative, Rat, > 5 mg/l /4h(Aerosol) (OECD 403)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

LC50, inhalative, Rat, > 5 mg/l/4h

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

Eye, non-irritating

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

non-irritating

Skin corrosion/irritation Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

dermal, non-irritating

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

non-irritating

Respiratory or skin sensitisation Toxicological data of complete product are not available.

May cause an allergic skin reaction.

Calculation method

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

dermal, non-sensitizing

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

dermal, non-sensitizing

Specific target organ toxicity — single exposure

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure

Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

NOAEC, inhalative, Rat, 980 mg/m³, no adverse effect observed

LOAEL, oral, Rat, 125 mg/kg bw/day, adverse effect observed

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOAEL, dermal, Rabbit, 1000 mg/kg bw/day

NOAEL, inhalative, Rat, 980 mg/m³ air

LOAEL, oral, Rat, 125 mg/kg bw/day

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

in vitro, negativ



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0

Page 10 / 15

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

in vitro, negativ

Reproduction toxicity

Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, negativ

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

- Development

Substance

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, negativ

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

11.2 Information on other hazards

Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

Other information non

none



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 11 / 15

SECTION 12: Ecological information

12.1 Toxicity

_			
D	ro	ึ่ง	 nt.

Based on the available information, the classification criteria are not fulfilled.

Substance

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0

EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)

LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)

NOEL, (21d), Daphnia magna, 10 mg/l (OECD 211)

NOEL, (72h), Pseudokirchneriella subcapitata, >= 100 mg/l (OECD 201)

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)

LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)

NOEL, (72h), Pseudokirchneriella subcapitata, >100 mg/l (OECD 201)

NOEL, (21d), Daphnia magna, 10 mg/l (OECD 211)

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

EL50, (72h), Pseudokirchneriella subcapitata, > 100 mg/l (OECD 201)

EL50, (48h), Daphnia magna, > 10000 mg/l (OECD 202)

LL50, (96h), Oncorhynchus mykiss, > 100 mg/l (OECD 203)

NOAEL, Oncorhynchus mykiss, > 1000 mg/l (14/28d)(QSAR Petrotox))

NOAEL, (21d), Daphnia magna, 10 mg/l (OECD 211)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOELR, (14d), fish, 1 g/L

LL50, (96h), fish, 100 mg/L

LL50, (96h), Invertebrates, 10 g/L

Distillates (petroleum), hydrotreated light naphthenic, CAS: 64742-53-6

EL50, (48h), Daphnia magna, > 1000 mg/l

LL50, (96h), Pimephales promelas, > 100 mg/l

NOEL, (72h), Pseudokirchneriella subcapitata, 100 mg/L (OECD 201. KS=2)

12.2 Persistence and degradability

Behaviour in environment compartments

Behaviour in sewage plantCan be separated out mechanically in purification plants.

Biological degradability The product is not readily biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 12 / 15

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150102 150104

150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

IMDG

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

IMDG

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 13 / 15

14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with

IMDG

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with not applicable

IMDG

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to

ADR/RID

nο

no

Inland navigation (ADN)

Marine transport in accordance with no

IMDG

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014

TRANSPORT-REGULATIONS ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2023)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK

REACH: GB CLP.

- Observe employment restrictions

for people

Observe employment restrictions for mothers-to-be and nursing mothers. Observe

employment restrictions for young people.

- VOC (2010/75/CE) not applicable



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0 Page 14 / 15

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par

Route

RID = Règlement concernant le transport international ferroviaire de marchandises

dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par

voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure Skin Sens. 1: H317 May cause an allergic skin reaction. (Calculation method)

Modified position SECTION 11 been added: Contains no ingredients with endocrine-disrupting properties.

SECTION 12 been added: Contains no ingredients with endocrine-disrupting properties.



Date printed 07.03.2023, Revision 07.03.2023

Version 13.0. Supersedes version: 12.0

Page 15 / 15