



1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO ATF MB14

VAICO No.:

V60-0216, V60-0217, V60-0218, V60-0219

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

- Excellent quality properties
- High load capacity, outstanding wear minimisation
- Exceptional friction coefficient consistency
- No foaming
- Very low evaporation loss
- Smooth gear shifting even at low temperatures
- Unrivalled viscosity-temperature behaviour
- Outstanding oxidation and thermal stability
- No adverse effect on standard sealing materials

3. USE INSTRUCTIONS

- Specially designed for use in new Mercedes-Benz 7-speed automatic transmissions (NAG2/model 722.9) up to 18/06/2010
- ATF MB 14 is also suitable for older Mercedes-Benz 5-speed automatic transmissions with controlled torque converter lockup clutch and rear wheel drive (NAG1/model 722.6) and is generally backward compatible with previous MB approval 236.12
- Observe manufacturer instructions!

4. PERFORMANCE DATA

4.1. Fit to*:

MB 236.14, 001 989 68 03, 001 989 68 03 10, 001 989 68 03 13



PRODUCT DATA



TYPICAL VALUES	METHOD	UNIT	VAICO ATF MB14
Density at 15°C	DIN 51 757	g/cm ³	0.850
Viscosity at 40°C	DIN ISO 3104	mm ² /s	31
Viscosity at 100°C	DIN ISO 3104	mm ² /s	6.2
Viscosity index (VI)	DIN ISO 2909	-	154
COC flash point	DIN ISO 2592	°C	>170
Pour point	DIN ISO 3016	°C	-42
Colour	-	-	red

* conforms to OEM specifications – The above values may vary within commercially accepted tolerances