

OFFICIALTECH

ATF LIFE PROTECT 8

22/05/2017
3016

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

APPLICATIONS

Exclusively intended for the ZF 6, 8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

FEATURES

Anti-wear protection : significantly extended transmission life.
Frictional properties : very smooth gear shifting, no vibration.
Extended oil life : excellent thermal and oxidation stability.

SPECIFICATION LEVEL

| | | | |
|----------|-------------|------------|------------|
| BMW | 83222152426 | JAGUAR | 02JDE26444 |
| CHRYSLER | 68157995AA | LAND ROVER | LR023288 |
| FIAT | 9.55550-AV5 | VW | G 060 162 |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|-------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.845 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 28.1 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 5.94 |
| Viscosity index | ASTM D2270 | | 164 |
| Pour point | ASTM D6892 | °C | -48 |
| Brookfield viscosity at -40°C | ASTM D2983 | mPa.s | 9500 |
| Flash Point COC | ASTM D92 | °C | 210 |
| Colour | VISUAL | | GREEN |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

