OEM SPECIFIC ATF LIFE PROTECT 6

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

APPLICATIONS

Mainly intended for the ZF-6 speed automatic transmissions, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid (e.g. Audi Quattro).

FEATURES

Anti-wear protection: significantly extended transmission life. Frictional properties: very smooth gear shifting, no vibration. Extended oil life: excellent thermal and oxidation stability.

SPECIFICATION LEVEL

AML 4G4319A509/AA/S **JAGUAR** Fluid 8432 **BENTLEY** PY112995PA LAND ROVER TYK500050 **BMW** M-1375.4 MASERATI 231603 vw G 055 005 **BMW** 83220142516 **HYUNDAI** 040000C90SG ZF TE-ML11

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.845
Kinematic viscosity at 40°C	ASTM D445	mm²/s	31.0
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.2
Viscosity index	ASTM D2270		153
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	9500
Flash Point COC	ASTM D92	°C	202
Colour	VISUAL		AMBER

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

