

ECO FLOW

MULTI VEHICLE ATF FE

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties : very smooth gear shifting, no vibration.

Anti-wear protection : significantly extended transmission life.

Extended oil life : excellent thermal and oxidation stability.

SPECIFICATION LEVEL

AISIN-WARNER	JWS 3324	HYUNDAI	SPH-IV
AISIN-WARNER	AW-1	JAGUAR	02JDE26444
BMW	M-1375.4	LAND ROVER	LR023288
BMW	83222152426	MAZDA	FZ
CHRYSLER	68157995AA	MB	236.12
FIAT	9.55550-AV2	MITSUBISHI	ATF J3
FIAT	9.55550-AV5	NISSAN	MATIC-S
FORD	MERCON SP	TOYOTA	AUTO FLUID WS
FORD	MERCON LV	VW	G 055 162
FORD	WSS-M2C924-A	VW	G 060 162
HONDA	DW-1	VW	G 055 005
HYUNDAI	NWS-9638 T5	VW	G 055 540
HYUNDAI	SP-IV		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	29.4
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.1
Viscosity index	ASTM D2270		162
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	9500
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		RED

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®