

TECHNICAL DATA SHEET



Type no.	725 11	
Article no.	010725110101	
EAN/GTIN no.	9005753009936	
Application	Starter battery	
Electrical data		
Rated voltage	12V	
Rated capacity	225 Ah (K20)	
Cold start current	1050 A (EN)	
Dimensions and weights		
Box	C	
Length max.	517mm	
Width max.	273mm	
Box height max.	212mm	
Total height max.	240mm	
Battery weight	Ca. 57,0 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	18	
Pallet ID	Euro pallet	
Items per layer	6	
		
Features		
Base hold-down	B00	
Layout	3	
Terminal	1	
Separator	PE bag separator	
Degassing	Battery with single degassing	
Flame arrester	Not integrated	
Performance identification	W4-C2-V3-E2	
Maintenance 1)		
Water consumption	W4	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 3 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage 2)	max. 14,8 V	

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2020-09-30 ; Rights relating to changes and errors retained.
original