


# TECHNICAL DATA SHEET



Type no.	957 51	
Article no.	010957510101	
EAN/GTIN no.	9005753010352	
Application	Long-term discharge battery	
<b>Electrical data</b>		
Rated voltage	12V	
Rated capacity	75 Ah(K5), 100 Ah(K20), 110 Ah(K100)	
<b>Dimensions and weights</b>		
Box	H8	
Length max.	354mm	
Width max.	175mm	
Box height max.	190mm	
Total height max.	190mm	
Battery weight	Ca. 24,0 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	48	
Pallet ID	Euro pallet	
Items per layer	12	
<b>Features</b>		
Base hold-down	B13	
Layout	0	
Terminal	1	
Separator	PE bag separator with glass nonwoven	
Degassing	Battery with central degassing	
Flame arrester	Integrated	
<b>Maintenance 1)</b>		
Water consumption	> 4g/Ah	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 9 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage 2)	max. 14,4 V	

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2020-09-30 ; Rights relating to changes and errors retained.  
original