


DONNEES TECHNIQUES

Courant de charge [A]	120
Type de réseau de bord	pour véhicules 12V
Type de poulie	PVR6
Pince	M8 B+
Connectique	PLUG650

PHOTOS



Bornes	
L	Lamp
DFM	

DOCUMENTS

BT-130 Refus des carcasses alternateurs/démarrateurs

APPLICATIONS

IVECO		
DAILY (00-06) - 2.8 29 L 9	84 ch	05.1999 >
DAILY (00-06) - 2.8 29 L 9 V	84 ch	05.1999 >
DAILY (00-06) - 2.8 29 L 11	105 ch	05.1999 >
DAILY (00-06) - 2.8 29 L 11 V	106 ch	05.1999 >
DAILY (00-06) - 2.8 29 L 13	125 ch	11.2001 >
DAILY (00-06) - 2.8 35 C/S 9	84 ch	05.1999 >
DAILY (00-06) - 2.8 35 C/S 9 V	84 ch	05.1999 >
DAILY (00-06) - 2.8 35 C/S 11	106 ch	05.1999 >
DAILY (00-06) - 2.8 35 C/S 11 V	106 ch	05.1999 >
DAILY (00-06) - 2.8 35 C/S 13	125 ch	05.1999 >
DAILY (00-06) - 2.8 35 C/S 13 V	125 ch	05.1999 >
DAILY (00-06) - 2.8 35 C 15	146 ch	11.2001 >
DAILY (00-06) - 2.8 35 C/S 15 V	146 ch	11.2002 >
DAILY (00-06) - 2.8 50 C 11	106 ch	05.1999 >
	106 ch	05.1999 >
DAILY (00-06) - 2.8 50 C 13	125 ch	05.1999 >
	125 ch	05.1999 >
DAILY (00-06) - 2.8 50 C 15	146 ch	01.2001 >
DAILY (00-06) - 2.8 65 C 15	146 ch	11.2001 > 04.2006