



INBOARD TECH 4T 15W50

Oil for Marine engines

Inboard gasoline 4 stroke

Technosynthese

TYPE OF USE

Specially designed for gasoline inboard 4 stroke engines.
Gasoline inboard engines : CRUSADER, MERCUISER, VOLVO PENTA, YAMAHA...
Suitable for Diesel inboard engines, turbocharged or not.

PERFORMANCES

STANDARDS API SH / SG / CD

Reinforced anti-friction properties by the MOTUL "Technosynthese" base stock to increase engine lifetime.

Exceeds the API SH standard level for gasoline engines.

High detergency and dispersive properties to prevent deposit formation in the engine.

Reinforced anti-corrosion additivation.

Anti-oxidant, anti-foam.

RECOMMENDATIONS

Oil change : According to manufacturers' recommendations and to be adjusted according to use and oil test results.

MOTUL INBOARD TECH 4T can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	15W-50
Density at 20°C (68°F)	ASTM D1298	0.874
Viscosity at 40°C (104°F)	ASTM D445	133.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	18.1 mm ² /s
Viscosity index	ASTM D2270	151
Flash point	ASTM D92	238°C / 460.4°F
Pour point	ASTM D97	-27°C / -16.6°F
TBN	ASTM D2896	9.9 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL. 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site : www.motul.fr

11/09