



You'll never run out of air again.

The ContiMobilityKit for extended movability.

- › Easy-to-use repair kit for sealing and reinflating a punctured tyre
- › Ensuring an unaltered driving performance for another 200 km at a maximum speed of 80 km/h
- › Original equipment quality 'Engineered in Germany'
- › Non-hazardous latex-based tyre sealant



The convenient solution to go.

The ContiMobilityKit is a convenient repair kit, designed to seal punctures in the tyre tread caused by nails or similar objects with a diameter of up to 6 mm. The kit consists of a compact compressor and a separate sealant bottle and has a shelf life of up to 5 years. In case of a puncture, an emergency roadside tyre change is not necessary and the journey can be continued for another 200 km at a maximum speed of 80 km/h. It's not even necessary to remove and replace the valve core - after just a few steps you are ready to go again. The ContiMobilityKit is only suitable for passenger car tyres with a mandatory maximum tyre pressure of 3 bar.

Product contents:

- > Compressor
- > Pressure-resistant tyre sealant bottle
- > User manual
- > Bag
- > Gloves

Technical specifications of compressor:

Amperage	Voltage	Maximum pressure
Max. 10 A according to DIN ISO 8820	12 V	700 kPa (7 bar, 102 psi)
Dimensions	Weight	Area of application
150 mm × 130 mm × 60 mm	650 g	-30°C to +60°C

Technical specifications of sealant bottle:

Sealant amount	Shelf life	Dimensions
450 ml	5 years	Ø 87 mm × 125 mm
Weight	Application temperature	
585 g	-30°C to +60°C	

Application for passenger car tyres:

The product can be used for the tyre dimensions which are shown in the following chart and with a required tyre pressure of up to 300 kPa (3 bar, 43 psi).

Tyre width in mm	Tyre cross section										Rim size in inches		
130	25-80										R 10		
195											R 14		
135/	25	30	35	40	45	50	55	60	65	70	75	80	R 15
145/	25	30	35	40	45	50	55	60	65	70	75	80	
155/	25	30	35	40	45	50	55	60	65	70	75	80	
165/	25	30	35	40	45	50	55	60	65	70	75	80	
175/	25	30	35	40	45	50	55	60	65	70	75	80	
185/	25	30	35	40	45	50	55	60	65	70	75	80	
195/	25	30	35	40	45	50	55	60	65	70	75	80	
205/	25	30	35	40	45	50	55	60	65	70	75		
215/	25	30	35	40	45	50	55	60	65	70			
225/	25	30	35	40	45	50	55	60	65				
235/	25	30	35	40	45	50	55	60					
245/	25	30	35	40	45	50	55						
155/	25	30	35	40	45	50	55	60	65	70	75	80	R 16
165/	25	30	35	40	45	50	55	60	65	70	75	80	
175/	25	30	35	40	45	50	55	60	65	70	75	80	
185/	25	30	35	40	45	50	55	60	65	70	75	80	
195/	25	30	35	40	45	50	55	60	65	70	75	80	
205/	25	30	35	40	45	50	55	60	65	70			
215/	25	30	35	40	45	50	55	60	65				
225/	25	30	35	40	45	50	55	60					
235/	25	30	35	40	45	50	55						
245/	25	30	35	40	45	50							
185/	25	30	35	40	45	50	55	60	65	70	75		R 17
195/	25	30	35	40	45	50	55	60	65	70			
205/	25	30	35	40	45	50	55	60	65				
215/	25	30	35	40	45	50	55	60	65				
225/	25	30	35	40	45	50	55	60					
235/	25	30	35	40	45	50	55						
245/	25	30	35	40	45	50							
255/	25	30	35	40	45								
265/	25	30	35	40									
275/	25	30	35										
285/	25	30	35										

Tyre width in mm	Tyre cross section										Rim size in inches		
205/	25	30	35	40	45	50	55	60					R 18
215/	25	30	35	40	45	50	55	60					
225/	25	30	35	40	45	50	55	60					
235/	25	30	35	40	45	50							
245/	25	30	35	40	45								
255/	25	30	35	40	45								
265/	25	30	35	40									
275/	25	30	35										
285/	25	30	35										
295/	25	30											
215/	25	30	35	40	45	50	55						R 19
225/	25	30	35	40	45	50	55						
235/	25	30	35	40	45	50							
245/	25	30	35	40	45								
255/	25	30	35	40									
265/	25	30	35										
275/	25	30	35										
225/	25	30	35	40	45								
235/	25	30	35	40	45								
245/	25	30	35	40									
255/	25	30	35										R 20
265/	25	30	35										
275/	25	30	35										
225/	25	30	35	40	45								
235/	25	30	35	40	45								