



Stay pumped - all along the journey.

Spare parts for the ContiMobilityKit:
the tyre sealant.

- › Replacement product of original equipment quality "Engineered in Germany"
- › Non-hazardous latex-based tyre sealant
- › Extended shelf life of up to five years
- › Sealant bottle can be disposed of in household waste
- › No need to remove and replace valve core



www.continental-mobility.com



Part number: 17120750000

Extended movability in case of a puncture.

The tyre sealant is pumped by the Continental compressor into the tyre, enabling the onward journey to the nearest garage or tyre service (max. 80 km/h and max. 200 km). It seals car tyre punctures caused by nails or similar objects with a diameter of up to 6 mm.

Product contents:

- › Pressure-resistant 450 ml tyre sealant bottle

Technical specifications of sealant bottle:

Sealant amount	Shelf life	Dimensions
450 ml	5 years	Ø 87 mm × 125 mm
Weight	Application temperature	
585 g	-30°C to +60°C	

Application for passenger car tyres:

The product can be used for the tyre dimensions which are shown in the following chart and with a required tyre pressure of up to 300 kPa (3 bar, 43 psi). 450 ml replacement bottles can be used as a replacement for ContiMobilityKit's 300 ml, 450 ml and 560 ml OE bottles (560 ml OE bottle depending on tyre dimensions - please see chart).

Tyre width in mm	Tyre cross section	Rim size in inches	
130 195	25-80	R 10 R 14	
135/	25 30 35 40 45 50 55 60 65 70 75 80	R 15	
145/	25 30 35 40 45 50 55 60 65 70 75 80		
155/	25 30 35 40 45 50 55 60 65 70 75 80		
165/	25 30 35 40 45 50 55 60 65 70 75 80		
175/	25 30 35 40 45 50 55 60 65 70 75 80		
185/	25 30 35 40 45 50 55 60 65 70 75 80		
195/	25 30 35 40 45 50 55 60 65 70 75 80		
205/	25 30 35 40 45 50 55 60 65 70 75		
215/	25 30 35 40 45 50 55 60 65 70		
225/	25 30 35 40 45 50 55 60 65		
235/	25 30 35 40 45 50 55 60		
245/	25 30 35 40 45 50 55		
155/	25 30 35 40 45 50 55 60 65 70 75 80		R 16
165/	25 30 35 40 45 50 55 60 65 70 75 80		
175/	25 30 35 40 45 50 55 60 65 70 75 80		
185/	25 30 35 40 45 50 55 60 65 70 75 80		
195/	25 30 35 40 45 50 55 60 65 70 75 80		
205/	25 30 35 40 45 50 55 60 65 70		
215/	25 30 35 40 45 50 55 60 65		
225/	25 30 35 40 45 50 55 60		
235/	25 30 35 40 45 50 55		
245/	25 30 35 40 45 50		
185/	25 30 35 40 45 50 55 60 65 70 75	R 17	
195/	25 30 35 40 45 50 55 60 65 70		
205/	25 30 35 40 45 50 55 60 65		
215/	25 30 35 40 45 50 55 60 65		
225/	25 30 35 40 45 50 55 60		
235/	25 30 35 40 45 50 55		
245/	25 30 35 40 45 50		
255/	25 30 35 40 45		
265/	25 30 35 40		
275/	25 30 35		
285/	25 30 35		

Tyre width in mm	Tyre cross section	Rim size in inches
205/	25 30 35 40 45 50 55 60	R 18
215/	25 30 35 40 45 50 55 60	
225/	25 30 35 40 45 50 55 60	
235/	25 30 35 40 45 50	
245/	25 30 35 40 45	
255/	25 30 35 40 45	
265/	25 30 35 40	
275/	25 30 35	
285/	25 30 35	
295/	25 30	
215/	25 30 35 40 45 50 55	R 19
225/	25 30 35 40 45 50 55	
235/	25 30 35 40 45 50	
245/	25 30 35 40 45	
255/	25 30 35 40	
265/	25 30 35	
275/	25 30 35	R 20
225/	25 30 35 40 45	
235/	25 30 35 40 45	
245/	25 30 35 40	
255/	25 30 35	
265/	25 30 35	

Last updated: 02/2016.