

THE NETHERLANDS



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval
- extension-of-type-approval
- refusal-of-type-approval
- withdrawal-of-type-approval

of a type of component (towing bracket) with regard to Directive 94/20/EC

Type-approval number: e4*94/20*0414*00

Reason for extension:

SECTION I

0.1	Make (trade name of manufacturer)	: Bosal
0.2.	Type and general commercial description(s)	: 023321
0.3.	Means of identification of type if marked on the component	: Approval nu

0.3.1. Location of the marking : on type plate

0.5. Name and address of manufacturer : Bosal
Postbus 168

 $$4920\ AD\ MADE$$ In the case of components and separate


technical units, location and method of affixing of the EEC approval mark : on type plate

0.8. Name(s) and address(es) of assembly plants : see information

document

: Approval number

(Annex III), item 0.8



0.7.

SECTION II

 Additional information (where applicable)

: see Appendix I

2. Technical sevice responsible for

carrying out the tests

: RDW

: 26-09-1996

Testbaan|Centrum Talingweg 76 8218 NX Lelystad

3. Date of test report


4. Number of test report : TCL-94/20-205/96

5. Remarks (if any) : see Appendix I

6. Place : Zoetermeer

7. Date • 11 N

8. Signature



- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request:
 - Application form relating to Annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Testreport, as mentioned in item 4.

651-4878

Appendix I

to EEC type-approval certificate No : e4*94/20*0414*00 concerning the component type-approval of mechanical coupling devices with regard to Directive 94/20/EC

1. Additional information

1.1. Class of the type of coupling : A50-X

1.2. Categories or types of vehicles for which the device is designed or restricted

see fitting instructions

1.3. Maximum D-value : 6.34 kN

1.4. Maximum vertical load S at the coupling point

: 50 kg

1.5. Maximum load U at the fifth wheel coupling point

-- ton

1.6. Maximum V-value : -- kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to

special types of vehicles : see fitting instructions

1.8. Information on the fitting of special towing brackets or mounting plates

see fitting instructions

5. Remarks :

The fitting of the towbar on the vehicle must be checked according annexI nr.5.10, according the presciptions mentionend in annex

VII

