



NEDERLAND  
(THE NETHERLANDS)



### EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

**Type-approval number: e4\*94/20\*1573\*00**


Reason for extension:

#### SECTION I

- 0.1. Make (trade name of manufacturer) : Bosal
- 0.2. Type and general commercial description(s) : 026412
- 0.3. Means of identification of type marked on the component : Approval number
- 0.3.1. Location of that marking : On type plate
- 0.5. Name and address of manufacturer : Bosal  
postbus 168  
4920 AD Made Nederland
- 0.7. In the case of components and separate technical units, location and method of affixing of the EEC type approval mark : On type plate
- 0.8. Address(es) of assembly plant(s) : See information document (annex III, item 0.8)

**Type-approval number: e4\*94/20\*1573\*00**

**SECTION II**

1. Additional information (where applicable) : See Appendix I
2. Technical service responsible for carrying out the tests : RDW  
Testbaan|Centrum  
Talingweg 76  
8218 NX Lelystad
3. Date of test report : 28-09-2000
4. Number of test report : RDW-94/20-1452
5. Remarks (if any) : See Appendix I
6. Place : Zoetermeer
7. Date : 12. OKT 2000
8. Signature :  M.L. Veenstra
9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request, is attached.
  - Application form relating to annex III and annexed drawings
  - Drawings and instructions for attachment
  - Fitting instructions
  - Test report as mentioned in item 4.

**Appendix I**  
**to EEC type-approval certificate No : e4\*94/20\*1573\*00**  
**concerning the components type-approval of mechanical coupling devices with regard to**  
**Directive 94/20/EEC**

1. Additional information
  - 1.1. Class of the type of coupling : A50-X
  - 1.2. Categories or types of vehicles for which the device is designed or restricted : See fitting instructions
  - 1.3. Maximum D-value : 8,50 kN
  - 1.4. Maximum vertical load S at the coupling point : 75 kg
  - 1.5. Maximum load U at the fifth wheel coupling point : ----- ton
  - 1.6. Maximum V-value : ----- kN
  - 1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles : See fitting instructions
  - 1.8. Information on the fitting of special towing brackets or mounting plates : See fitting instructions
  
5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.