



NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*1839*00

Reason for extension:

SECTION I

0.1. Make (trade name of manufacturer) : Bosal

0.2. Type and general commercial description(s) : 027201

0.3. Means of identification of type marked on the

component

0.3.1. Location of that marking : On type plate

0.5. Name and address of manufacturer : Bosal

postbus 168

: Approval number

4920 AD Made Nederland

0.7. In the case of components and separate technical: On type plate

units, location and method of

Address(es) of assembly plant(s)

affixing of the EEC type approval mark

: See information document

(annex III, item 0.8)

0.8.

Type-approval number: e4*94/20*1839*00

SECTION II

1. Additional information (where applicable) : See Appendix I

2. Technical service responsible for carrying out

the tests

RDW

Testbaan|Centrum

Talingweg 76 8218 NX Lelystad

3. Date of test report : 08-08-2001

4. Number of test report : RDW-94/20-1975

5. Remarks (if any) : See Appendix I

6. Place : Zoetermeer

7. Date : 08-08-2001

8. Signature : _ _ _ _

J.P.M. Laumen

9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request, is attached.

- Application form relating to annex III and annexed drawings
- Drawings and instructions for attachment
- Fitting instructions
- Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No: e4*94/20*1839*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1.1. Class of the type of coupling : A50-X

1.2. Categories or types of vehicles for which : See fitting instructions the device is designed or restricted

1.3. Maximum D-value : 13,5 kN

1.4. Maximum vertical load S at the coupling point : 120 kg

1.5 Maximum load U at the fifth wheel : ---- ton

coupling point
Maximum V-value

1.6.

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles

1.8 Information on the fitting of special towing : See fitting instructions brackets or mounting plates

5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.



kN