



## **BOLL PTFE GREASE**

The PTFE lubricant is a high quality product on the basis of oils, PTFE and solvents. This is a substance that lubricates, penetrates and protects against unfavourable weather conditions. It has been developed for long-term lubrication in heavy duty operation. The product reduces and eliminates friction and wear and tear of the lubricated parts. It protects against water, moisture, salt, acids, dirt, dust, sand, etc. The lubricant was specially developed to lubricate parts subject to high pressure, shocks and vibration. The product protects every moving part leaving a transparent lubricant layer.

### **Application:**

Carefully clean and degrease and dry the place to be lubricated. Before use, shake the container for about 3 minutes. Evenly apply a thin lubricant layer. After use, turn over the container and spray until the valve is empty.

### **Physical properties:**

general description:	mixture of mineral oil, PTFE and admixtures
physical state:	liquid
density:	0.9172
Colour	light yellow
Odour:	specific
Operating temperature, ° C:	-50 do 200
Propellant:	propane / butane
Density (20 ° C), g / ml	0.722
Pressure (20 ° C), bar	2.9
Output (20 ° C), g / s	1.5

### **Comments:**

*All technical specifications are approximate. We recommend to test the material to make sure it is appropriate for the specific application. The producer reserves the right to improve the product and change its technical properties, including modifications to the specification.*